

AMENDMENT OF SOLICITATION / MODIFICATION OF CONTRACT			1. Contract Number	Page of Pages 1 2	
2. Amendment/Modification Number DCKT-2011-B-0061-0001	3. Effective Date 3/9/11	4. Requisition/Purchase Request No.	5. Solicitation Caption Wreckers		
6. Issued by: Office of Contracting and Procurement Transportation and Specialty Equipment Commodity Group 2000 14 th Street NW, 6 th Floor Washington, DC 20009		Code	7. Administered by (If other than line 6)		
8. Name and Address of Contractor (No. street, city, county, state and zip code)		Code	Facility	9A. Amendment of Solicitation DCKT-2011-B-0061	
				X	9B. Dated (See Item 11) 2/17/11
					10A. Modification of Contract Order No.
					10B. Dated (See Item 13)
11. THIS ITEM ONLY APPLIES TO AMENDMENTS OF SOLICITATIONS					
<input type="checkbox"/> The above numbered solicitation is amended as set forth in item 14. The hour and date specified for receipt of Offers <input checked="" type="checkbox"/> is extended. <input type="checkbox"/> is not extended. Offers must acknowledge receipt of this amendment prior to the hour and date specified in the solicitation or as amended, by one of the following methods: (a) By completing Items 8 and 15, and returning <u>1</u> copies of the amendment; (b) By acknowledging receipt of this amendment on each copy of the offer submitted; or (c) BY separate letter or fax which includes a reference to the solicitation and amendment number. FAILURE OF YOUR ACKNOWLEDGMENT TO BE RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIPT OF OFFERS PRIOR TO THE HOUR AND DATE SPECIFIED MAY RESULT IN REJECTION OF YOUR OFFER. If by virtue of this amendment you desire to change an offer already submitted, such may be made by letter or fax, provided each letter or telegram makes reference to the solicitation and this amendment, and is received prior to the opening hour and date specified.					
12. Accounting and Appropriation Data (If Required)					
13. THIS ITEM APPLIES ONLY TO MODIFICATIONS OF CONTRACTS/ORDERS, IT MODIFIES THE CONTRACT/ORDER NO. AS DESCRIBED IN ITEM 14					
A. This change order is issued pursuant to (Specify Authority): The changes set forth in Item 14 are made in the contract/order no. in item 10A.					
B. The above numbered contract/order is modified to reflect the administrative changes (such as changes in paying office, appropriation data etc.) set forth in item 14, pursuant to the authority of 27 DCMR, Chapter 36, Section 3601.2.					
C. This supplemental agreement is entered into pursuant to authority of:					
D. Other (Specify type of modification and authority)					
E. IMPORTANT: Contractor <input type="checkbox"/> is not <input checked="" type="checkbox"/> is required to sign this document and return <u>1</u> copies to the issuing office.					
14. Description of Amendment/Modification (Organized by UCF Section headings, including solicitation/contract subject matter where feasible.) Solicitation DCKT-2011-B-0061 is amended to provide additional specifications and detail as outlined on Page 2 of this amendment. The bid submission date is changed to March 17, 2011 at 2:00 pm.					
Except as provided herein, all terms and conditions of the document referenced in item (9A or 10A) remain unchanged and in full force and effect.					
15A. Name and Title of Signer (Type or print)		16A. Name of Contracting Officer Gena Johnson			
15B. Name of Contractor (Signature)	15C. Date Signed	16B. District of Columbia  (Signature of Contracting Officer)	16C. Date Signed 3/9/11		

2. Amendment/Modification Number	3. Effective Date	4. Requisition/Purchase Request No.	5. Solicitation Caption
DCKT-2011-B-0061-0001	3/9/11		Wreckers

1. Section C.2.2.1.5 is revised to reflect there will be a minimum of 160 inches and a maximum of 178 inches for the Extended Reach past Tailboard (w/fork), and the underneath wheel-lift capacity should be a maximum 17,500 lbs
2. ADD Section C.2.2.1.12 Integrated recovery boom mounted in the body. The recovery boom must have twin winches with a 35,000lb lifting capacity.
3. ADD Section C.2.2.1.13 Integrated outriggers for stability.
4. Section B.3 Price Schedule is revised to add CLIN 0003: One (1) 2011 Recovery/Tow Truck with Self Loading Quick-Pick Wheel Lift with Galvaneal Body. See Attachment No.1 to this amendment for revised Price Schedule; and Attachment No. 2 – Specifications for Recovery/Tow Truck with Self Loading Quick-Pick Wheel Lift.

SECTION B: SUPPLIES OR SERVICES AND PRICE

B.1 The Government of the District of Columbia, Office of Contracting and Procurement, Transportation and Specialty Equipment Commodity Group, on behalf of the Department of Public Works (DPW), is seeking a contractor to provide wreckers.

B.2 The District contemplates award of a firm fixed price contracts. The District will award a single contract for each Contract Line Item listed in B.3 below.

B.3 PRICE SCHEDULE

Contract Line Item Number (CLIN)	Supplies or Services	Quantity	Unit Price	Total Price
0001	2011 Heavy Duty & Roll-Back (Recovery), Truck, International 7600, Tandem Axles or Equal (No Third Rear Axle) as specified in Section C.2.1	2	\$ _____	\$ _____
0002	2011 Heavy Duty Single Axle Wrecker, 25 Ton GVWR as specified in Section C.2.2 (including revised specification in Amendment No. 1)	1	\$ _____	\$ _____
0003	2011 Recovery/Tow Truck with Self Loading Quick-Pick Wheel Lift with Galvaneal Body as specified in Amendment No. 1, Attachment No. 2)	1	\$ _____	\$ _____

Specification
**Recovery/Tow Truck with Self Loading Quick-Pick Wheel Lift with Galvaneal
Body**

1. Contractor Data

- | | | |
|------|--|-----------------|
| 1.1 | One (1) copy of manufacture's statement of origin for the motor vehicle | Required |
| 1.2 | One (1) copy of the operators manual | Required |
| 1.3 | One (1) copy of the shop manual | Required |
| 1.4 | One (1) copy mounted equipment. Shop manual | Required |
| 1.5 | One (1) copy of the electrical and vacuum technical manual | Required |
| 1.6 | One (1) copy of the parts book with illustrated parts breakdown (IPB) | Required |
| 1.7 | One (1) copy of mounted equipment. Parts book with (IPB) | Required |
| 1.7a | List of critical parts that are needed for initial preventative maintenance program | Required |
| 1.8 | One (1) CD Rom (to include the shop manual, electrical and vacuum Technical manual and parts book with (IPB) | Required |
| 1.9 | Four (4) sets of keys | Required |

2. Warranty

- | | | |
|-----|--|-----------------|
| 2.1 | Bidder shall state manufacture's normal warranty _____ | Required |
| 2.2 | Bidder shall state mounted equipment manufacture's normal warranty _____ | Required |

3 Safety Equipment

- | | | |
|-----|---|-----------------|
| 3.1 | First Aid Kit: Mounted in cab
(State model offered) _____ | Required |
| 3.2 | 2.5 lb. ABC dry chemical type, fire extinguisher mounted in cab | Required |
| 3.3 | 10 lb. ABC dry chemical type, fire extinguisher mounted in right front horizontal compartment | Required |
| 3.4 | Triangle Kit | Required |

- 3.5 Back-up alarm: Horn or buzzer type **Required**
- 3.6 Dual note horn **Required**
- 3.7 Air horn **Required**
- 3.8 Driver and Passenger Airbags **Required**

4. **Vehicle**

- 4.1 Ford F-550, 4X4 or equal **Required**
(State make and model offered) _____
- 4.2 Wheelbase: Maximum: 165 inches **Required**
(State wheelbase offered) _____
- 4.3 Color: Bright White or equal **Required**

5. **Gross Vehicle Weight Rating (GVWR)**

- 5.1 Minimum: 17,000 pounds **Required**
(State GVWR Offered) _____
- 5.2 Front axle weight rating: minimum: 7,000 **Required**
(State front axle weight rating) _____
- 5.3 Weight Distribution Chart: All bidders are **REQUIRED** to supply a **Required**
Factory certified weight distribution chart, showing the weight on each
Of the axles **EMPTY** and **FULLY LOADED**
- 5.4 Cab to Axle: Minimum: 60 inches **Required**
(State inches offered) _____

6. **Chassis**

- 6.1 Frame Type: Ladder, Stable Platform **Required**
- 6.2 Color: Black **Required**
- 6.3 Front bumper: Heavy duty minimum: 24" height **Required**
- 6.4 Front tow hooks: 2 **Required**
- 6.5 Power windows and door locks **Required**
- 6.6 Running Board; Diamond Plate **Required**
- 6.7 Push Bumper: Front with rubber cushion 24" height. Width: 75th **Required**

- | | | |
|------------|---|-----------------|
| 6.8 | Self loading dollies | Required |
| 6.9 | Public address system | Required |
| 6.10 | Convenience group simulators | Required |
| 6.11 | Five switch "power-up" switch panel or equal | Required |
| 7. | <u>Suspension</u> | |
| 7.1 | Front type: Heavy Duty Shock Absorbers | Required |
| 7.2 | Bidder shall state front springs capacity | Required |
| 7.3 | Rear type: Heavy Duty Shock Absorbers
(State make and model offered) _____ | Required |
| 8. | <u>Wheels</u> | |
| 8.1 | Spare: 19.5 inch polished aluminum | Required |
| 9. | <u>Tires</u> | |
| 9.1 | Front: All weather | Required |
| 9.2 | Rear: Mud + Snow | Required |
| 9.3 | Spare; Mud + Snow | Required |
| 10. | <u>Steering</u> | |
| 10.1 | Full Power steering | Required |
| 10.2 | Steering column: Tilting | Required |
| 11. | <u>Brakes</u> | |
| 11.1 | Type: 4- wheel ABS | Required |
| 11.2 | Parking brake type: Standard manufacture | Required |
| 12. | <u>Engine</u> | |
| 12.1 | Type: 6.0 Liter Diesel or equal
(State make and model offered) _____ | Required |
| 12.2 | Cold Weather Start; Automatic integrated aid start system | Required |
| 12.3 | Net S.A.E. minimum horsepower: 235 @ rated RPM | Required |

(State horse power offered) _____

12.4 Torque: Minimum: 500 torque lbs @ rated RPM
(State torque offered) _____ **Required**

12.5 Automatic engine shut down system: **Required**
Protection to include: Low oil pressure, low coolant level and high engine temperature
(State system offered) _____

12.6 Induction system: Turbocharger, intercooler **Required**

13. Cooling System

13.1 Coolant: Permanent type antifreeze with protection to -34 degrees Fahrenheit **Required**

13.2 Pressurized series flow **Required**

14. Transmission

14.1 Type: minimum 4 speed automatic **Required**
(State make and model offered) _____

14.2 Transmission cooler **Required**

14.3 Electric shift on the fly 4x4 **Required**

15. Clutch Pump

15.1 Clutch pump; Dewees type with momentary switch **Required**

15.2 Clutch Pump: Single pump to minimum generate seven (7 gallons per minute (GPM) @ 1000 RPM'S **Required**

16. Differential

16.1 Limited slip rear axle **Required**

17. Electrical

17.1 Dual 12 Volt negative ground **Required**

17.2 Battery: Minimum: 750 cca/78 amp **Required**

17.3 Alternator: minimum: Single 200 amp or equal **Required**

17.4 OEM idle control for manual operation **Required**

18. Fuel System

18.1 Fuel tank: minimum: 38 U.S. gallons **Required**
(State capacity offered) _____

18.2 Separator: heated water/fuel **Required**

18.3 Vehicle shall be equipped with an EJ Ward Candometer (VIT) automated fuel system. **Required**

Contact: Lee Christensen
EJ Ward Inc.
Phone: (210) 824-7383

19. Exhaust System

19.1 Horizontal with heat shield **Required**

20. Exterior

20.1 Color: White **Required**

21. Interior

21.1 Color: painted surface, white **Required**

21.2 Color: non-painted surface, gray **Required**

22. Seating

22.1 Heavy-Duty Cloth full bench seat **Required**

23. Insulation

23.1 Manufacturer's sound package not to exceed 79 decibel prior to body Installation **Required**

24. Heat/Defrost/Air Conditioner

24.1 Multi-speed **Required**

24.2 Manual CFC free (R134-A) **Required**

25. Instrumentation

25.1 Hour meter **Required**

25.2 Transmission temperature gauge **Required**

- 25.3 Air intake restriction gauge **Required**
26. **Radio**
- 26.1 AM/FM Stereo CD Player/digital clock **Required**
27. **Mirrors**
- 27.1 Hood/fender: OEM tow mirror package **Required**
- 27.2 Left door: Heated power foldaway with 8" Convex below **Required**
- 27.3 Right door: heated power foldaway with remote control and 8" convex below **Required**
- 27.4 Down view mirror: top of right door **Required**
- 27.5 Rear view mirror: inside cab **Required**
28. **Body (Heavy Duty: Minimum: 86 inches Wide) (Galvaneal Body)**
- 28.1 Body must conform to the cab **Required**
- 28.2 Hot Century Express 312 self loading Tow Truck with recovery boom or equal **Required**
(State make and model offered) _____
- 28.3 Color: Bright white paint to be rust resistant **Required**
- 28.4 Conspicuity tape: each side and rear **Required**
- 28.5 Hydraulic Hook-up: Clutch pump delete PTO **Required**
- 28.6 In-cab remote control pendant on cord w/4 functions **Required**
- 28.7 Safety Straps: one (1) pair **Required**
- 28.8 Basket Straps: one (1) pair **Required**
- 28.9 Safety Chains: in rear pockets **Required**
- 28.10 Two (2) side storage compartments **Required**
- 28.11 Mud Guards: rear of rear axle **(NO ADVERTISEMENT)** **Required**
- 28.12 Power Boom Elevation w/ holding valve **Required**
- 28.13 Wiring Harness with Junction Box **Required**

28.14	Dual Controls: Each side	Required
28.15	Power Fold for Stinger Storage	Required
28.16	Self Centering Crossbar with 3" Pivot Pin	Required
28.17	Roller guided Hose Tacking system	Required
28.18	Tow Sling	Required
28.19	Dolly-Aluminum Constructed-mount on top back of the body	Required
	a. Tire Size 4.80 - 8	
28.20	<u>Capacities/ratings</u>	
	a. Lift Rating: minimum: 4,000 lbs.	Required
	b. Tow Rating; minimum: 7,500 lbs.	Required
	c. Wheel Lift:	Required
	d. Retracted distance from Tailgate: minimum: 41"	Required
	e. Extended distance form Tailgate: minimum: 74"	Required
	f. Maximum Hydraulic Extension: minimum: 29"	Required
	g. Dual Winch System: Variable Speed: Dual 18,000 lbs. each	Required
	h. Air release free wheel	Required
	I. Cable tensioners	Required
	j. Cable: Extra improved plow steel 6x37 IWRC	Required
	k. Diameter	Required
	l. Length	Required
	m. Boom: Light height form ground to hook at minimum boom elevation:	Required
	n. R-83" / E-116" boom rating at boom swivel:	Required
	(R) etracted – 16,000 lbs. minimum	
	(E) xtended – 4,000 lbs. minimum	
29.	<u>Lighting</u>	
29.1	Light Plyon	Required
29.2	Four (4) head hide-away strobe system (Blue/White)	Required
29.3	Eight (8) head strobe light bar light, all blue/white lens front and rear 54" whelen light bar, liberty series	Required
29.4	Two (2) six 6 inch chrome upper work lights	Required
29.5	Lower work lights	Required