

REQUEST FOR QUOTATIONS (RFQ) (THIS IS NOT AN ORDER)			PAGE OF 1	PAGES 3	
1. RFQ NO. DCTO-2009-Q-0056	2. DATE ISSUED 11-18-08	3. REQUISITION NO. RQ488622	4. TYPE OF MARKET <input type="checkbox"/> Open <input checked="" type="checkbox"/> Set Aside (CBE) <input type="checkbox"/> Open with Subcontracting Set Aside		
5A. ISSUED BY:  Government of the District of Columbia (District) Office of Contracting and Procurement Information Technology Group 441 4 <sup>th</sup> Street N.W., Suite 971 North Washington, D.C. 20001			6. DELIVERY <b>Ten (10) business days from award date.</b>		
5B. FOR INFORMATION CALL: (Name and telephone no.) (No collect calls) Leon T. Borroum, Contract Specialist, Phone (202) 727-6793, fax (202) 727-1679 leon.borroum@dc.gov			7. DELIVERY METHOD  <input checked="" type="checkbox"/> FOB DESTINATION <input type="checkbox"/> OTHER (See Schedule)		
8A. TO: NAME AND ADDRESS, INCLUDING ZIP CODE, OF QUOTER			9. DESTINATION FOR DELIVERY OF GOODS OR SERVICES ORDERED  Joshua Jack Emergency Management Agency 2720 Martin Luther King, Jr. Ave., SE Washington, DC 20032		
8B. TAX ID NO. OF QUOTER:					
10. PLEASE FURNISH QUOTATIONS ON OR BEFORE: <b>November 21 2008</b> , 2:00 PM, BID ROOM, 441 4 <sup>th</sup> Street. N.W. Suite 703 or email: leon.borroum@dc.gov		11A. PLEASE STATE YOUR LSDBE CERTIFICATION NUMBER BELOW (Attach Copy)			
		11B. IF YOU HAVE A DISTRICT OF COLUMBIA SUPPLY SCHEDULE (DCSS) CONTRACT FOR THESE ITEMS, PLEASE ENTER THE CONTRACT NUMBER BELOW:			
<b>12. INSTRUCTIONS TO QUOTERS AND TERMS AND CONDITIONS</b>					
<b>Instructions to Quoters:</b> Please complete Blocks 8B, 11A, 11(B) if applicable, 13(E), 13(F), 14, 15, 16, 17, 18, as well as submission of technical and price quotations as outlined in this solicitation, submit one (1) original and three (3) copies of <u>signed</u> quotations to Office of Contracting and Procurement, 441 4 <sup>th</sup> Street, NW, Suite 703 (Bid Room), Washington, D.C. 20001. This is the <u>only</u> authorized method of submitting a quotation for this RFQ. All quotations must be received no later than the date and time stated in block 10 of this RFQ.					
<b>Terms and Conditions:</b> SEE ATTACHED.					
<b>13. SCHEDULE (Include applicable Federal, State and local taxes and all delivery charges)</b>					
ITEM NO. (A)	SUPPLIES/SERVICES (B)	QUANTITY (C)	UNIT (D)	UNIT PRICE (E)	AMOUNT (F)
	<b>See attached Statement of Work</b>				
0001	<b>Axis Blade Encoder.</b> <b>Models - AXIS 241Q - Part Number: 241S</b>  <b>Specification:</b>  Axis Blade Encoder. Models - AXIS 241Q*: Four video channels AXIS 241S*: One video channel *Also available as blade versions for Axis Video Rack Solution. Video compression - MPEG-4 Part 2 (ISO/IEC 14496-2) Motion JPEG. Resolutions - 160x120 to 704x576. Frame rate - MPEG-4 AXIS 241Q: Up to 20/17 (NTSC/PAL) fps at CIF. AXIS 241S: Up to 30/25 (NTSC/PAL) fps at 2CIF, 21/17 fps at 4CIF. Frame rate Motion JPEG - AXIS 241Q: Up to 30/25 (NTSC/PAL) fps at CIF, AXIS 241S: Up to 30/25 (NTSC/PAL) fps at 4CIF. Video streaming - Simultaneous MPEG-4 and Motion JPEG, Controllable frame rate and bandwidth VBR/CBR MPEG-4.	98	EA	\$	\$

	<p>Image settings - Compression, color, rotation, aspect ratio correction, mirroring, Text and image overlay  Privacy mask, De-interlace filter  Pan/Tilt/Zoom</p> <p>m - Wide range of analog PTZ cameras supported (drivers available for download at <a href="http://www.axis.com">www.axis.com</a>), 20 presets/camera, Guard tour, PTZ control queue, Supports Windows compatible joysticks.</p> <p>Security - Password protection, IP address filtering, HTTPS encryption, IEEE 802.1X network access control, digest authentication, user access log</p> <p>Supported protocols - IPv4/v6, HTTP, HTTPS, QoS layer 3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS.</p> <p>Application Programming Interface - Open API for software integration, including VAPIX® from Axis Communications available at <a href="http://www.axis.com">www.axis.com</a>.</p> <p>Intelligent video - Video motion detection, active tampering alarm.</p> <p>Alarm triggers - Intelligent video, external inputs, video loss.</p> <p>Alarm events - File upload via FTP, HTTP and email</p> <p>Notification via email, HTTP and TCP, External output activation.</p> <p>Video buffer - 9 MB pre- and post-alarm per channel</p> <p>Casing - Metal casing Standalone, stackable or with brackets for wall or cage mount.</p> <p>Processors and memory - AXIS 241Q: ARTPEC-2, 64 MB RAM, 8 MB Flash, AXIS 241S: ARTPEC-2, 32 MB RAM, 8 MB Flash.  Power - 7 20 V DC, max 8 W.</p>				
0002	<p><b>Axis 19 in Chassis, 14 Slot 4U.  Expansion - Part Number Q7900</b></p> <p><b>Specification:</b></p> <p>Axis 19 in Chassis, 14 Slot 4U.  Expansion slots - 14 slots for Axis video encoder blades.  Casing - 4U, 19-inch metal casing for rack mounting.  Power - 100-240 V AC, max. 480 W, 2 exchangeable, redundant power supply units.  Connectors - 4 Ethernet  10BaseT/100BaseTx/1000BaseT ports, RJ-45 (Gigabit Ethernet); use 1, 2, 3 or 4 Ethernet</p>	7	EA	\$	\$

	<p>ports depending on the bandwidth requirement, 14 terminal blocks, each with inputs/outputs, RS-485, half-duplex, 12 V power out.  Cooling - 3 replaceable fan cassettes.  Operating conditions - 0-45 °C (32-113 °F)  Humidity 20-80% RH (non-condensing).  Approvals - EN 55022 Class B, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, VCCI Class B, AS/NZ CISPR 22, ICES-003, UL, cUL, EN 60950-1.  Weight - 7550 g (16.6 lb.) excluding blades.  Included accessories - Installation Guide, mounting kit, 2 AC power cables, terminal blocks.</p>				
TOTAL AMOUNT					\$
14. NAME AND ADDRESS OF QUOTER ( <i>Street, city, county, State and ZIP Code</i> )	15. SIGNATURE OF PERSON AUTHORIZED TO SIGN QUOTATION (ELECTRONIC SIGNATURES <b>NOT</b> ACCEPTABLE)	16. DATE OF QUOTATION			
	17. NAME AND TITLE OF SIGNER ( <i>Type or print</i> )	18. TELEPHONE NO. ( <i>Include area code</i> )			